




DOOR BELL
DUAL TONE

双音门铃 1/2 声 IC



FEATURES 功能叙述

- TG: OSH.
- DING: 780 Hz \pm 30%.
- DONG: 625 Hz \pm 30%.

P/N	OPT	TIME
M60	VSS	1 声
M602	X	2 声

APPLICATION 产品应用



- Doorbell , Musical instrument , Toys.

ELECTRICAL CHARACTERISTICS 电气规格

(@V_{DD}=3V unless otherwise specified)

Characteristics	Sym.	Min.	Typ.	Max.	Unit	REMARKS
工作电压 Operating Voltage	V _{DD}	—	3	4.5	V	
工作电流 Operating Current	I _{OP}	—	0.1	0.5	mA	No load
静态电流 Quiescent Current	I _{SB}	—	1	5	μ A	
推动电流 OUT Driving Current	I _O	1	—	—	mA	@V _{DS} =1V
振荡频率 Oscillator Frequency	F _{OSC}	—	50	—	KHz	External \pm 30%, R _{osc} = 510K Ω
工作温度 Operating Temperature	Temp.	0	25	60	$^{\circ}$ C	

APPLICATION DIAGRAM 参考电路图




*All specs and applications shown above subject to change without prior notice.

(以上电路及规格仅供参考,本公司得径行修正)




DOOR BELL
DUAL TONE

双音门铃 1/2 声 IC

DOOR BELL	
M60/M602	

PAD ASSIGNMENT & POSITION



Unit: um

NO	NAME	X	Y
1	VDD	-508	375
2	X / OSC1	-218	375
3	Y / OSX2	228	375
4	OUT	508	375
5	VSS	508	-216
6	OPT	508	-375
7	E2 / ENV2	111	-375
8	E1 / ENV1	-118	-375
9	TG	-508	-375

* CHIP SIZE ~ 1.27 x 1.0 mm²

* IC substrate should be connected to VDD in PCB (PCB 上 IC 必须接 VDD)

*All specs and applications shown above subject to change without prior notice.

(以上电路及规格仅供参考,本公司得径行修正)



DOOR BELL
DUAL TONE

双音门铃 1/2 声 IC

DOOR BELL	
M60/M602	

PACKAGE OUTLINE

SYMBOLS	MIN	MAX
A	0.053	0.069
A1	0.004	0.010
A2		0.059
D	0.189	0.196
E	0.150	0.157
H	0.228	0.244
L	0.016	0.050
θ	0	8

Unit: INCH

SOP-8

SYMBOLS	MIN.	NOM.	MAX.
A	—	—	0.210
A1	0.015	—	—
A2	0.125	0.130	0.135
D	0.355	0.365	0.400
E	0.300 BSC.		
E1	0.245	0.250	0.255
L	0.115	0.130	0.150
e	0.335	0.355	0.375
θ	0	7	15

Unit: INCH

DIP-8

*All specs and applications shown above subject to change without prior notice.

(以上电路及规格仅供参考,本公司得径行修正)